



SUPERWINCH 'PRO' SERIES WINCH RANGE CONFORMS TO BS EN 14492-1 POWER DRIVEN WINCHES

PRO
EN 14492-1

www.superwinch.com

Winch shown for illustration purposes only



Husky **PRO** Electric

PROFESSIONAL WINCH SPECIFICATION

Features:

EU spec Line Pull: 24.5kN, (2,500kg)
Design Line Pull: 37.8kN, (3,860kg)
10:1 D:d ratio Rope Drum

Wire Rope:

2:1 safety factor

Wire Rope Fixing:

Twin hole safety feature

Gearing:

Heavy Duty Worm & Wormwheel set

Load Limiter:

Factory set thermal overload cut out

Labelling:

Rating Plate showing 1st layer and 4th layer figures
Fairlead warning label

Brake:

Irreversible worm and wormwheel action,
Full load-holding brake



PRO SPECIFICATION

	HUSKY-PRO
Rated Line Pull (EU), Bottom Layer	24.5 kN (2,500 kg)
Design Line Pull	37.8 kN (3,860 kg)
Line Speed, Bottom Layer, (No Load)	7.8 m/min
Wire Rope Diameter, Recommended	8 mm (5 tonne min break)
Wire Rope Length, Max	30 m
Drum Dimensions	72mm min dia x 228 mm long
Motor, 12v	1.43 kW (1.9 hp)
Motor, 24v	1.60 kW (2.1 hp)
Weight, Winch only	37 kg

PRO PERFORMANCE

HUSKY-PRO	12v	24v
Amp Draw at 0 kg	55	30
Amp Draw at 2,500 kg	240	140
Line Pull, 2nd Layer	20.5 kN (2,090 kg)	20.5 kN (2,090 kg)
Line Pull, 3rd Layer	17.65 kN (1,800 kg)	17.65 kN (1,800 kg)
Line Pull, 4th Layer	15.7 kN (1,600 kg)	15.7 kN (1,600 kg)

PROFESSIONAL WINCH	Part No.	
	12v	24v
Husky-PRO, Winch only	8514PRO	8515PRO
Husky-PRO, Roller Fairlead & Wire Rope	8552PRO	8553PRO
Husky-PRO, Roller Fairlead & Mount Plate	8532PRO	8533PRO

OPTIONAL ACCESSORIES	Part No.
Roller Fairlead	8584
Cable Tensioner	5605
Mount Plate	7840
Pulley Block, 9000kg	7750
Bow Shackle	0509
Battery Cables, 2m	256012
Isolator Switch	8370
Emergency Stop Switch	4-132-047
Solenoid operated contactor, 12v	4-124-115
Solenoid operated contactor, 24v	4-124-114
Rope Drum Safety Guard, Standard	85-30176
Rope Drum Safety Guard, Short	85-30177

WIRE ROPES	Part No.
Wire Rope, 8mm x 23m	8780
Wire Rope, 8mm x 30m	200005

PRO DIMENSIONS

